



TERRAMAC® RT9 PERSONNEL CARRIER



Chauffeur Your Crew with Ease

Transporting people on a job site can be a challenge but the Terramac® Personnel Carrier makes it a cinch! With a maximum capacity greater than any other carrier in its class you will save time and money.

The Terramac® RT9 is an all terrain utility vehicle that is easily maneuvered over rough, soft and steep ground conditions. With a carrying capacity of 18,000 pounds you will have more than enough power to move your crew.

Features

- 25 person capacity with seat-belts
- ROPS & FOPS certified
- 4 tool boxes accessible from outside
- Fold-down stairs with handrails
- Fully enclosed options available with heat



T189PC1

TERRAMAC® RT9 PERSONNEL CARRIER

Standard RT9 Specs*

PERFORMANCE

Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	2.5 mph
Travel Speed - 2nd Gear	5.4 mph
Gradeability	58% (32°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	6.4 PSI
Ground Pressure (unloaded)	3.8 PSI

HYDRAULICS

Transmission	HST
Drive Pump Max Flow (x2)	43 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (AUX Output)	25 gpm @ 3000 PSI
Rear Section (HST Drive)	22 gpm @ 550 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

ENGINE

Manufacturer	Cummins
Model	QSB 6.7 T4F
Displacement	408 cu. in.
Horsepower	225 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA ea.
Fuel Capacity	64 gallons

DIMENSIONS

Full Length	19' 6"
Full Height	9' 11"
Width Over Tracks	8' 3"
Min Ground Clearance	21"
Front Overhang	2' 6"
Track Gauge (Center-to-Center)	6'
Track Width	27.5"
Undercarriage Length	
(Idle to Drive Hub)	12' 3"
Machine Weight (no bed)	21,500 lbs.
Machine Weight (with bed)	26,000 lbs.

* Based on standard machine. Specifications will vary based on optional equipment selected.

Personnel Carrier Specs

DIMENSIONS

178" L x 102" W x 83" H

WEIGHT

7,000 LBS.

SEAT LAYOUT

