

TERRAMAC D14XL WATER TANK



Water On Demand

When water is required at the jobsite, rely on the Terramac D14XL wheeled dumper with 3,000-gallon water tank for efficient and reliable transport. With a low-profile chassis and 600mm tires this unit handles uneven terrain with ease. From concrete mixing to site cleaning to soil compaction, ensuring water is available keeps projects on schedule and workers and equipment operating safely.

EQUIPMENT FEATURES

- (2) front hydraulically controlled spray heads
- (2) rear hydraulically controlled spray heads
- 200 gpm tank mounted water cannon with joystick control
- 3,000-gallon steel water tank with interior epoxy coating
- 50' of 1-1/2" hose with nozzle on rear of unit
- 3" ground fill pipe for easy ground filling
- 600mm tires provide site access and smooth ride
- 21.7 mph travel speed ensures efficient delivery



TERRAMAC D14XL WATER TANK

D14XL with Water Tank Specs

PERFORMANCE

Travel Speed - 4th Gear	21.7 mph
Gradeability	40% (22°)
Tires	600mm/50R 22.5 Alliance

HYDRAULICS

Transmission	4-speed HST
Drive Pump Max Flow	47.3 GPM
Drive Pump Max Pressure	6,962 PSI
AUX Pump	16.5 GPM
Steering and Brake Pump	12.7 GPM

ENGINE

Manufacturer	Perkins
Model	904J-E36TA T4F
Horsepower	121 HP
Electrical System	12 V
Battery	(1) 12V 50Ah, 1000 CCA AGM
Fuel Capacity	46.2 Gallons

DIMENSIONS

Overall Length	17' 9"
Overall Height	10' 6"
Overall Width	8' 4"
Min Ground Clearance	1' 5"
Frame Type	Rigid
Turning Radius	16' 11"
Approach Angle	35°
Front Axle	8° Oscillating Automatic Limited Slip Planetary Reduction at Hubs
Rear Axle	Fixed; Fully Locking Differential Planetary Reduction at Hubs
Machine Weight (empty)	13,600 lbs.
Machine Weight (full)	44,465 lbs.

* Based on standard machine. Specifications will vary based on optional equipment selected.

Water Tank Specs

SPRAY CONTROLS

Front Spray Heads	(2) hydraulically controlled
Rear Spray Heads	(2) hydraulically controlled
Water Cannon	Joystick controlled
Hose Reel	(50') 1-1/2" hose with nozzle mounted on rear of tank
Water Pump	4 X 3 hydraulically driven from chassis system
Ladder	Mounted on rear of tank
All Controls	Mounted in cab and operated separately

OTHER FEATURES

Tank Size	3,000-gallon
Tank Material	Steel with interior epoxy coating
Tank Filling	Ground fill pipe

OPTIONS (NOT INCLUDED IN PRICE)

Electric hose reel
Self-filling (drafting) option