

TERRAMAC RT9 WITH FLAT BED

Standard RT9 with Flat Bed Specs

The Terramac RT9 with flat bed features an 18,000 lb. carrying capacity and is a versatile unit that travels effortlessly across any type of terrain. The flat bed allows heavy-duty hauling for oversized cargo and features side loading options for maximum site convenience.

DIMENSIONS	
Full Length	21' 7"
Full Height	9' 11"
Width Over Tracks	8' 3"
Min Ground Clearance	21"
Front Overhang	2' 6"
Track Gauge (Center-to-Center)	6'
Track Width	27.5"
Undercarriage Length (Idler to Drive Hub)	12' 3"
Flat Bed Loading Height Over Side	4' 8"
Width of Flat Bed	7' 10"
Length of Flat Bed	13' 4"
Frame Rail Top to Bulkhead	4' 3"
Dumping Angle	60°
Machine Weight (no bed)	22,368 lbs.
Machine Weight (with rock bed)	26,180 lbs.

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7 T4F
Displacement	408 cu. in.
Horsepower	225 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA each
Fuel Capacity	64 gallons



HYDRAULICS	
Transmission	HST
Drive Pump Max Flow (x2)	43 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (AUX Output)	25 gpm @ 3000 PSI
Rear Section (HST Drive)	22 gpm @ 550 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

PERFORMANCE	
Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	3.6 mph
Travel Speed - 2nd Gear	6.6 mph
Maximum Gradability	58% (30°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	6.4 PSI
Ground Pressure (unloaded)	3.8 PSI